



Cleaner thinking. Greener solutions.

Product Specification

VH1 S3000_5S Valved Head

Applications

- Hot and cold water dispensers (including Office Coffee Services and water boilers)
- High volume, high flow
- Removal of Chlorine, Taste, Odour (CTO) and Particulate
- Scale inhibition

Product Benefits

- Re-usable cartridge based system results in significant reduction in carbon footprint and cost
- Hygienic, sealed filter system prevents contamination at all times
- Valved head allows rapid, dry change of replacement cartridge
- Produces cleaner, safer, better tasting water
- Scale inhibition helps protect equipment from the harmful effects of hard water - reduces maintenance and down time
- Higher capacity filter giving enhanced volume and flow rate

Product Specifications

Cartridge Part Number	VH1-C S3000_5S
Capacity	3000 US gal / 11,356 L
Flow Rate (per minute)	1 US gal / 3.8 L
Degree of Filtration	5 micron nominal
Min Water Temperature	39°F / 4°C
Max Water Temperature	100°F / 38°C
Min Water Pressure	10 psi / 0.7 bar
Max Water Pressure	120 psi / 8.5 bar
Inlet / Outlet	1/4" integral push fitting
Height (incl head)	10 3/4" / 273mm
Diameter	3 1/16" / 78mm
Fittings	1/4" integral or bspt

3 1/16"
78mm

10 3/4"
273mm (max)



Accreditations

- NSF 42 - CTO & Particulate
- WRAS approved



Visit www.NSF.org or www.eco3filtration.com for the claims associated with products that are NSF listed



Environmentally Friendly



Reusable



Hygienic



Six Sigma Protocol



WRAS Approved



Cleaner thinking. Greener solutions.



Installation/Replacement Tips

- On installation allow room around the clamp ring to grip and rotate
- Minimum 30mm vertical clearance below base of housing for cartridge change
- On replacing cartridge in sump, align arrow on cartridge top metal plate with arrow on sump – insert and rotate clockwise as per “IN” arrow to stop
- To reconnect to head, align arrows on head and sump, push sump into head and rotate clamp ring anti-clockwise
- Apply new change date label over existing main product label

Operation Tips

- Change cartridge at not more than 6 monthly intervals
- Change cartridges when capacity is reached or when pressure falls below 10 psi
- Flush for 2 litres following initial installation and cartridge change

Warranty

eco3 systems (excluding replacement cartridges) are covered by a limited warranty against defects in material and workmanship for a period of 5 years after date of purchase. Replacement cartridges are covered by a limited warranty against defects in materials and workmanship for a period of 1 year after date of purchase.

Warning

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Install in cold water applications only. The contaminants removed by this water filter are not necessarily present in all water. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

We recommend regular replacement of the filter cartridges - change the cartridge at least every 6 months.

Do not install if water pressure exceeds 120 psi. If your water pressure exceeds 80 psi, you must install a pressure limiting valve. Do not install where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for these conditions. Installation and use must comply with all State and local plumbing laws and regulations. Improper installation may result in property damage due to water leakage.

For replacement parts or further product information contact

www.eco3filtration.com | UK & Europe: +44 161 941 6003
USA: +1 877 291 0330



Icon Technology Systems Limited, The Court House, Altrincham, WA14 1DU, UK
PO Box 801208, 5330 Brookstone Drive, NW STE 250, Acworth, GA 30101, USA